

0390203266

# **AHC2 Two-stage motor with Transmission**



For reliable performance in reduced size: The Bosch compact geared motors are the appropriate solution for industrial applications with limited space. These drives exhibit high power density and cover a broad field of 12 and 24V requirements. Bosch offers different speed/torque characteristic curves and various mechanical interfaces.

• Degree of protection: IP 50

Operating mode: S2

Rotation direction: Left and right

rotation

Nominal voltage: 12 V












Contact us!

# **Product Specification**

#### Technical data and performance curve



Nominal power (W): 3,5

Nominal current (A): 4,2

Nominal speed (rpm): 22,25

Nominal torque (Nm): 1,5

Stall torque (Nm): 23

**Transmission ratio:** 185,5:1


Hall Sensor: No

Transmission position: Right






#### **Dimensions**




Please contact us if you need a 3d model

Contact

# Circuit diagram



### Connector



## **Housing:**

TE 968182-1

Locker:

TE 968183-1


PIN:

TE JPT 0-927768-1

, ming is



#### **Drive interface**



#### Features and benefits

- Rotation in both direction: The Bosch small geared motors can be used as a drive
- Available with hall sensor: For positioning or direction of rotation feedback
- Production in line with the original automotive quality guidelines: For proven quality, high reliability and a long service life
- Operating mode S2 or S3: Suitable for short-term or intermittent operation

#### Downloads

You may also be interested in:

To Product family: Catalogue

